

McKAT

CLEVIS SLING HOOK



DESCRIPTION

- Designed to use with grade 80 alloy steel chain.
- All clevis hooks are individually inspected and tested with proof load.
- Embossed forged marking for WLL, SIZE, CE and McKAT
- Spares are available for load pin and safety latch.

Standard:	BS EN 1677
Material:	Alloy Steel
FOS:	4:1
Heat Treatment:	Quenched & tempered
Proof Load:	At 200 % of WLL
Colour Code:	Red



Forged Marking




Heavy Duty Cast Latch



High Tensile Alloy Steel Load Pin

DIAGRAM:



MCKAT CLEVIS SLING HOOK SPECIFICATION:

ARTICLE NO.	WLL (T)	A (mm)	B (mm)	D (mm)	H (mm)	K (mm)	E (mm)	NET WT. (kg)
MHC-08	2	9.5	37	37	32.5	85.5	29	0.52
MHC-10	3.15	13	49	46	35	104	39	1.05
MHC-13	5.3	16.5	56.5	56	42.5	128	47	2
MHC-16	8	21.5	70.5	60	54	150	55	3.7
MHC-20	12.5	24	77	79	58	180	61	6
MHC-22	15	27	91	101	62	213	72	10.4
MHC-26	21.2	30	117	115	75	250	85	14.5
MHC-32	31.5	35	150	140	88	317	106	27